

SECTION 1: Product identifier

1.1. GHS Product identifier

Product form	: Mixture
Product name	: Spot Marking Paint - Fluoro Colours (Red, Blue, Orange, Pink, Green, Yellow, Purple)
Product code	: 11811 11812 11813 11814 11815 11816 11817

1.2. Other means of identification

Synonyms	: Aerosol Marking Paint
----------	-------------------------

1.3. Recommended use of the chemical and restrictions on use

Recommended use	: Use according to manufacturer's directions. Application is by spray atomisation from a hand held aerosol pack.
Restrictions on use	: Not to be used for any purpose other than the one the product was designed for

1.4. Details of manufacturer or importer

Supplier

Signet Pty Ltd
56 Ingleston Rd
WAKERLEY, QLD 4154
Australia
T +61 (07) 3179 2100
sales@signet.net.au - www.signet.net.au

1.5. Emergency phone number

Emergency number	: Office hours: +61 (07) 3179 2100 Poisons Information Centre (24 h): 13 11 26
------------------	---

SECTION 2: Hazard identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Aerosol, Category 1	H222;H229
Serious eye damage/eye irritation, Category 2A	H319

2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU)	:  Flame Exclamation mark
Signal word (GHS AU)	: Danger
Contains	: Aerosol Ethanol 100% (30 – 60 %); Ethyl Acetate (< 30 %); Acrylic Resin (< 10 %)
Hazard statements (GHS AU)	: H222 - Extremely flammable aerosol H229 - Pressurised container: May burst if heated H319 - Causes serious eye irritation
Precautionary statements (GHS AU)	: P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P103 - Read carefully and follow all instructions. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Spot Marking Paint - Fluoro Colours (Red, Blue, Orange, Pink, Green, Yellow, Purple)

Safety Data Sheet

according to the WHS Regulations

P251 - Do not pierce or burn, even after use.
P264 - Wash hands, forearms and face thoroughly after handling.
P280 - Wear eye protection, protective clothing, protective gloves.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
Additional hazard statements (GHS AU) : AUH044 - Risk of explosion if heated under confinement.
Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition and information on ingredients

Name	CAS-No.	%
Aerosol Ethanol 100%	-	30 – 60
Ethyl Acetate	141-78-6	< 30
Limestone	1317-65-3	< 10

SECTION 4: First aid measures

4.1. Description of necessary first-aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin with plenty of water.
First-aid measures after eye contact : Rinse immediately with plenty of water. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Symptoms caused by exposure

Symptoms/effects after eye contact : Eye irritation.

4.3. Medical attention and special treatment

Other medical advice or treatment : Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Unsuitable extinguishing media are not known.

5.2. Specific hazards arising from the chemical

Fire hazard : Extremely flammable aerosol.
Explosion hazard : Pressurised container: May burst if heated.
General measures : No action shall be taken without appropriate training or involving any personal risk. Notify authorities if product enters sewers or public waters.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

Spot Marking Paint - Fluoro Colours (Red, Blue, Orange, Pink, Green, Yellow, Purple)

Safety Data Sheet

according to the WHS Regulations

5.3. Special protective equipment and precautions for fire-fighters

- | | |
|--------------------------------|---|
| Firefighting instructions | : Exercise caution when fighting any chemical fire. Keep upwind. Fight fire from safe distance and protected location. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion. |
| Protection during firefighting | : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. |

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- | | |
|---|---|
| General measures | : No action shall be taken without appropriate training or involving any personal risk. Notify authorities if product enters sewers or public waters. |
| 6.1.1. For non-emergency personnel | |
| Emergency procedures | : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes. |
| 6.1.2. For emergency responders | |
| Protective equipment | : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection". |

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and materials for containment and cleaning up

- | | |
|-------------------------|-------------------------------------|
| Methods for cleaning up | : Mechanically recover the product. |
|-------------------------|-------------------------------------|

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- | | |
|-------------------------------|--|
| Precautions for safe handling | : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid contact with skin and eyes. Wear personal protective equipment. |
| Hygiene measures | : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. |

7.2. Conditions for safe storage, including any incompatibilities

- | | |
|------------------------------|--|
| Technical measures | : Does not require any specific or particular technical measures. |
| Storage conditions | : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well-ventilated place. Keep cool. |
| Information on mixed storage | : Store away from incompatible materials and products. Refer to the detailed list of incompatible materials in section 10 Stability/Reactivity. |
| Storage area | : Keep out of direct sunlight. |
| Special rules on packaging | : Position containers so that any labeling information is visible. Keep packaging closed when not in use. Check containers and packaging regularly for leaks and damage. |
| Packaging materials | : Keep only in original packaging. |

SECTION 8: Exposure controls and personal protection

8.1. Control parameters - exposure standards

Spot Marking Paint - Fluoro Colours (Red, Blue, Orange, Pink, Green, Yellow, Purple)

Safety Data Sheet

according to the WHS Regulations

Ethyl Acetate (141-78-6)

Australia - Occupational Exposure Limits

Local name	Ethyl acetate (Acetic acid ethyl ester; Acetic ester)
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)

Limestone (1317-65-3)

Australia - Occupational Exposure Limits

OES TWA [1]	10 mg/m ³
Remark (AU)	This value is for inhalable dust containing no asbestos and < 1% crystalline silica

8.2. Monitoring methods

Monitoring methods	: Workplace exposure - General requirements for the performance of procedures for the measurement of chemical agents. Gas detectors should be used when flammable gases/vapours may be released.
--------------------	--

8.3. Engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station. Use spark-/explosionproof appliances and lighting system. Use grounded electrical/mechanical equipment. Handle product within a closed system.
----------------------------------	---

8.4. Individual protection measures, such as personal protective equipment (PPE)

Personal protective equipment	: Personal protective equipment (PPE) must be suited to the nature of the work and any hazard associated with the work as identified by the risk assessment conducted. Avoid all unnecessary exposure. Ocular shower with suitable liquid.
Hand protection	: Wear protective gloves
Eye protection	: Wear eye protection: Chemical goggles or safety glasses
Skin and body protection	: Wear protective clothing: Long sleeved protective clothing
Respiratory protection	: If mist is formed : Disposable half mask

Personal protective equipment symbol(s)



Consumer exposure controls	: Personal protective equipment (PPE) is not required when handling individual retail pack.
Other information	: PPE compliant to the recommended standards should be selected. The following Australian and New Zealand Standards will provide general advice regarding safety clothing and equipment: Respiratory equipment: AS/NZS 1715, Protective Gloves: AS 2161, Industrial Clothing: AS2919, Industrial Eye Protection: AS1336 and AS/NZS 1337, Occupational Protective Footwear: AS/NZS2210.

SECTION 9: Physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol.
Molecular mass	: Not applicable
Colour	: Various colours
Odour	: Not available
Odour threshold	: No data available
pH	: Not applicable
pH solution	: Not available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point / Freezing point	: Melting point: Not available
Boiling point	: Not available
Flash point	: -81 °C (hydrocarbon propellant).

Spot Marking Paint - Fluoro Colours (Red, Blue, Orange, Pink, Green, Yellow, Purple)

Safety Data Sheet

according to the WHS Regulations

Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
Flammability	: No data available
Vapour pressure	: Vapour pressure: Not available
Relative density	: Relative vapour density at 20°C: Not available. (Air=1).
Density	: Density: ≈ 0.8 kg/l Relative density: (Water = 1).
Solubility	: Water: immiscible
Partition coefficient n-octanol/water (Log Pow)	: Not available
Viscosity, kinematic	: Not available
Explosive properties	: Pressurised container: May burst if heated.
Explosive limits	: No data available
Minimum ignition energy	: No data available
VOC content	: Not available
Fat solubility	: No data available

SECTION 10: Stability and reactivity

Reactivity	: Extremely flammable aerosol. Pressurised container: May burst if heated.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Incompatible materials	: Strong acids. Strong bases. Strong oxidizers.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Ethyl Acetate (141-78-6)

LD50 oral	5620 mg/kg bodyweight
LD50 dermal	> 18000 mg/kg bodyweight
LC50 Inhalation - Rat (Dust/Mist)	57700 mg/l

Skin corrosion/irritation	: Not classified pH: Not applicable
Serious eye damage/irritation	: Causes serious eye irritation. pH: Not applicable
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified

Ethyl Acetate (141-78-6)

STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

Spot Marking Paint - Fluoro Colours (Red, Blue, Orange, Pink, Green, Yellow, Purple)

Vaporizer	Aerosol
Viscosity, kinematic	Not available

Spot Marking Paint - Fluoro Colours (Red, Blue, Orange, Pink, Green, Yellow, Purple)

Safety Data Sheet

according to the WHS Regulations

Ethyl Acetate (141-78-6)	
Animal studies and expert judgment for classification	False
Limestone (1317-65-3)	
Animal studies and expert judgment for classification	False
Aerosol Ethanol 100%	
Animal studies and expert judgment for classification	False

SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

12.1. Ecotoxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

Ethyl Acetate (141-78-6)	
EC50 - Other aquatic organisms [1]	717 mg/l waterflea
EC50 - Other aquatic organisms [2]	3300 mg/l

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Spot Marking Paint - Fluoro Colours (Red, Blue, Orange, Pink, Green, Yellow, Purple)	
Partition coefficient n-octanol/water (Log Pow)	Not available

12.4. Mobility in soil

Spot Marking Paint - Fluoro Colours (Red, Blue, Orange, Pink, Green, Yellow, Purple)	
Partition coefficient n-octanol/water (Log Pow)	Not available

12.5. Other adverse effects

Ozone	: Not classified
Other adverse effects	: No additional information available

Spot Marking Paint - Fluoro Colours (Red, Blue, Orange, Pink, Green, Yellow, Purple)	
Fluorinated greenhouse gases	False
Ethyl Acetate (141-78-6)	
Fluorinated greenhouse gases	False
Limestone (1317-65-3)	
Fluorinated greenhouse gases	False
Aerosol Ethanol 100%	
Fluorinated greenhouse gases	False

Spot Marking Paint - Fluoro Colours (Red, Blue, Orange, Pink, Green, Yellow, Purple)

Safety Data Sheet

according to the WHS Regulations

SECTION 13: Disposal considerations

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

ADG	IMDG	IATA
14.1. UN number		
1950	1950	1950
14.2. UN Proper Shipping Name		
AEROSOLS	AEROSOLS	Aerosols, flammable
14.3. Transport hazard class(es)		
2.1	2.1	2.1
		
14.4. Packing group		
Not applicable	Not applicable	Not applicable
14.5. Environmental hazards		
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No

14.6. Special precautions for user

Specific storage requirement : No data available
Shock sensitivity : No data available

14.7. Additional information

Other information : No supplementary information available

Transport by road and rail

UN-No. (ADG) : 1950
Special provision (ADG) : 63, 190, 277, 327, 344, 381
Limited quantities (ADG) : See SP 277
Excepted quantities (ADG) : E0
Packing instructions (ADG) : P207, LP200
Special packing provisions (ADG) : PP87, L2

Transport by sea

UN-No. (IMDG) : 1950
Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959
Packing instructions (IMDG) : P207, LP200
Special packing provisions (IMDG) : PP87, L2
EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG) : None
Stowage and handling (IMDG) : SW1, SW22
Segregation (IMDG) : SG69

Air transport

UN-No. (IATA) : 1950
PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Y203

Spot Marking Paint - Fluoro Colours (Red, Blue, Orange, Pink, Green, Yellow, Purple)

Safety Data Sheet

according to the WHS Regulations

PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

14.8. Hazchem or Emergency Action Code

Hazchem Code	: Not applicable
--------------	------------------

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question

Australian Industrial Chemicals Introduction Scheme (AICIS)

Australian Inventory of Industrial Chemicals (AICIS) : Listed
Inventory) status

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Relevant Poisons Schedule number : Unscheduled

15.2. International agreements

No additional information available

SECTION 16: Other information

Indication of changes:

Update of the SDS from former GHS version to the 7th edition of the GHS (GHS 7).

Data sources	: Safe Work Australia - Code of Practice - Preparation of Safety Data Sheets for Hazardous Chemicals Safe Work Australia - Code of Practice - Labelling of Workplace Hazardous Chemicals Safe Work Australia - Workplace Exposure Standards for Airborne Contaminants Safe Work Australia - Hazardous Chemical Information System (HCIS) Australian Inventory of Industrial Chemicals (AICIS Inventory) Environmental Protection Authority - Hazardous Substances (Hazard Classification) Notice 2020 Environmental Protection Authority - Hazardous Substances (Safety Data Sheets) Notice 2017 Environmental Protection Authority - Hazardous Substances (Labelling) Notice 2017 New Zealand - Chemical Classification and Information Database (CCID) New Zealand - Inventory of Chemicals (NZIoC) European Chemicals Agency (ECHA) - Annex VI (C&L Inventory) European Chemicals Agency (ECHA) - REACH Study Results European Chemicals Agency (ECHA) - REACH Registration Dossiers United Nations - Globally Harmonised System of Classification and Labelling of Chemicals (GHS) Uniform Scheduling of Medicines and Poisons (SUSMP) United Nations Recommendations on the Transport of Dangerous Goods (UNRTDG Model Regulation) Australian Dangerous Goods Code (ADG Code) International Air Transport Association Dangerous Goods Regulations (IATA DGR) International Maritime Dangerous Goods (IMDG Code).
Date of revision	: 12/07/2023

Classification

Aerosol 1	H222;H229
-----------	-----------

Spot Marking Paint - Fluoro Colours (Red, Blue, Orange, Pink, Green, Yellow, Purple)

Safety Data Sheet

according to the WHS Regulations

Classification	
Eye Irrit. 2A	H319

Full text of H-statements	
Aerosol 1	Aerosol, Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 2	Flammable liquids, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness

Safety Data Sheet (SDS), Australia

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

Spot Marking Paint - Black, Red, Blue, Green, Yellow, White, Orange, Grey, Purple, Lemon, Cream

Safety Data Sheet

according to the WHS Regulations

Issue date: 9/02/2023 Date of revision: 12/07/2023 Supersedes: 14/03/2023 Version: 1.2

SECTION 1: Product identifier

1.1. GHS Product identifier

Product form	: Mixture
Product name	: Spot Marking Paint - Black, Red, Blue, Green, Yellow, White, Orange, Grey, Purple, Lemon, Cream
Product code	: 11801 11802 11803 11804 11805 11806 11807 11808 11809 11810 11818

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use	: Application is by spray atomisation from a hand held aerosol pack. Use according to manufacturer's directions.
Restrictions on use	: Not to be used for any purpose other than the one the product was designed for

1.4. Details of manufacturer or importer

Supplier

Signet Pty Ltd
56 Ingleston Rd
WAKERLEY, QLD 4154
Australia
T +61 (07) 3179 2100
sales@signet.net.au - www.signet.net.au

1.5. Emergency phone number

Emergency number	: Office hours: +61 (07) 3179 2100 Poisons Information Centre (24 h): 13 11 26
------------------	---

SECTION 2: Hazard identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Aerosol, Category 1	H222;H229
Serious eye damage/eye irritation, Category 2A	H319
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336

2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU)	:	 
		Flame Exclamation mark
Signal word (GHS AU)	:	Danger
Contains	:	Ethyl Acetate (10 – 60 %); Acrylic Resin (10 – 30 %); Aerosol Ethanol 100% (< 30 %); High Mol Wt Wetting Agent (< 10 %)
Hazard statements (GHS AU)	:	H222 - Extremely flammable aerosol H229 - Pressurised container: May burst if heated H319 - Causes serious eye irritation H336 - May cause drowsiness or dizziness

Spot Marking Paint - Black, Red, Blue, Green, Yellow, White, Orange, Grey, Purple, Lemon, Cream

Safety Data Sheet

according to the WHS Regulations

Precautionary statements (GHS AU)	: P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P103 - Read carefully and follow all instructions. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P251 - Do not pierce or burn, even after use. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash hands, forearms and face thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area. P280 - Wear eye protection, protective clothing, protective gloves. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Additional hazard statements (GHS AU)	: AUH066 - Repeated exposure may cause skin dryness or cracking. AUH044 - Risk of explosion if heated under confinement.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition and information on ingredients

Name	CAS-No.	%
Ethyl Acetate	141-78-6	10 – 60
Acrylic Resin	-	10 – 30
Aerosol Ethanol 100%	-	< 30
High Mol Wt Wetting Agent	-	< 10

SECTION 4: First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	: Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Symptoms caused by exposure

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after eye contact	: Eye irritation.

4.3. Medical attention and special treatment

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Unsuitable extinguishing media are not known.

5.2. Specific hazards arising from the chemical

Fire hazard	: Extremely flammable aerosol.
Explosion hazard	: Pressurised container: May burst if heated.

Spot Marking Paint - Black, Red, Blue, Green, Yellow, White, Orange, Grey, Purple, Lemon, Cream

Safety Data Sheet

according to the WHS Regulations

- | | |
|--|---|
| General measures | : No action shall be taken without appropriate training or involving any personal risk. Notify authorities if product enters sewers or public waters. |
| Hazardous decomposition products in case of fire | : Toxic fumes may be released. |

5.3. Special protective equipment and precautions for fire-fighters

- | | |
|--------------------------------|---|
| Firefighting instructions | : Exercise caution when fighting any chemical fire. Keep upwind. Fight fire from safe distance and protected location. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion. |
| Protection during firefighting | : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. |

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- | | |
|------------------|---|
| General measures | : No action shall be taken without appropriate training or involving any personal risk. Notify authorities if product enters sewers or public waters. |
|------------------|---|

6.1.1. For non-emergency personnel

- | | |
|----------------------|---|
| Emergency procedures | : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. |
|----------------------|---|

6.1.2. For emergency responders

- | | |
|----------------------|---|
| Protective equipment | : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection". |
|----------------------|---|

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and materials for containment and cleaning up

- | | |
|-------------------------|-------------------------------------|
| Methods for cleaning up | : Mechanically recover the product. |
|-------------------------|-------------------------------------|

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- | | |
|-------------------------------|---|
| Precautions for safe handling | : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment. |
| Hygiene measures | : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. |

7.2. Conditions for safe storage, including any incompatibilities

- | | |
|------------------------------|--|
| Technical measures | : Does not require any specific or particular technical measures. |
| Storage conditions | : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool. |
| Information on mixed storage | : Store away from incompatible materials and products. Refer to the detailed list of incompatible materials in section 10 Stability/Reactivity. |
| Storage area | : Keep out of direct sunlight. |
| Special rules on packaging | : Position containers so that any labeling information is visible. Keep packaging closed when not in use. Check containers and packaging regularly for leaks and damage. |
| Packaging materials | : Keep only in original packaging. |

Spot Marking Paint - Black, Red, Blue, Green, Yellow, White, Orange, Grey, Purple, Lemon, Cream

Safety Data Sheet

according to the WHS Regulations

SECTION 8: Exposure controls and personal protection

8.1. Control parameters - exposure standards

Ethyl Acetate (141-78-6)

Australia - Occupational Exposure Limits

Local name	Ethyl acetate (Acetic acid ethyl ester; Acetic ester)
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)

8.2. Monitoring methods

Monitoring methods	: Workplace exposure - General requirements for the performance of procedures for the measurement of chemical agents. Gas detectors should be used when flammable gases/vapours may be released.
--------------------	--

8.3. Engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station. Use spark-/explosionproof appliances and lighting system. Use grounded electrical/mechanical equipment. Handle product within a closed system.
----------------------------------	---

8.4. Individual protection measures, such as personal protective equipment (PPE)

Personal protective equipment	: Personal protective equipment (PPE) must be suited to the nature of the work and any hazard associated with the work as identified by the risk assessment conducted. Avoid all unnecessary exposure. Ocular shower with suitable liquid.
Hand protection	: Wear protective gloves
Eye protection	: Wear eye protection: Chemical goggles or safety glasses
Skin and body protection	: Wear protective clothing: Long sleeved protective clothing
Respiratory protection	: Wear appropriate mask

Personal protective equipment symbol(s)



Consumer exposure controls	: Personal protective equipment (PPE) is not required when handling individual retail pack.
Other information	: PPE compliant to the recommended standards should be selected. The following Australian and New Zealand Standards will provide general advice regarding safety clothing and equipment: Respiratory equipment: AS/NZS 1715, Protective Gloves: AS 2161, Industrial Clothing: AS2919, Industrial Eye Protection: AS1336 and AS/NZS 1337, Occupational Protective Footwear: AS/NZS2210.

SECTION 9: Physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol; not miscible with water.
Molecular mass	: Not applicable
Colour	: Various colours
Odour	: Not available
Odour threshold	: No data available
pH	: Not applicable
pH solution	: Not available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point / Freezing point	: Melting point: Not available
Boiling point	: Not available
Flash point	: -81 °C (hydrocarbon propellant).
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available

Spot Marking Paint - Black, Red, Blue, Green, Yellow, White, Orange, Grey, Purple, Lemon, Cream

Safety Data Sheet

according to the WHS Regulations

Flammability	: No data available
Vapour pressure	: Vapour pressure: Not available
Relative density	: Relative vapour density at 20°C: Not available. (Air=1).
Density	: Density: ≈ 0.8 kg/l Relative density: (Water = 1).
Solubility	: Water: immiscible
Partition coefficient n-octanol/water (Log Pow)	: Not available
Viscosity, kinematic	: Not available
Viscosity, dynamic	: < 10 cP
Explosive properties	: Pressurised container: May burst if heated.
Explosive limits	: No data available
Minimum ignition energy	: No data available
VOC content	: Not available
Fat solubility	: No data available

SECTION 10: Stability and reactivity

Reactivity	: Extremely flammable aerosol. Pressurised container: May burst if heated.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Incompatible materials	: Strong acids. Strong bases. Strong oxidizers.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Ethyl Acetate (141-78-6)

LD50 oral	5620 mg/kg bodyweight
LD50 dermal	> 18000 mg/kg bodyweight
LC50 Inhalation - Rat (Dust/Mist)	57700 mg/l

High Mol Wt Wetting Agent

LC50 Inhalation - Rat [ppm]	0 ppm
LC50 Inhalation - Rat (Dust/Mist)	> 5 mg/l/4h
LC50 Inhalation - Rat (Vapours)	> 20 mg/l/4h

Skin corrosion/irritation	: Not classified pH: Not applicable
Serious eye damage/irritation	: Causes serious eye irritation. pH: Not applicable
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.

Ethyl Acetate (141-78-6)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

Acrylic Resin

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

Spot Marking Paint - Black, Red, Blue, Green, Yellow, White, Orange, Grey, Purple, Lemon, Cream

Safety Data Sheet

according to the WHS Regulations

STOT-repeated exposure : Not classified

High Mol Wt Wetting Agent

STOT-repeated exposure	May cause damage to organs (digestive tract) through prolonged or repeated exposure (oral).
------------------------	---

Aspiration hazard : Not classified

Spot Marking Paint - Black, Red, Blue, Green, Yellow, White, Orange, Grey, Purple, Lemon, Cream

Vaporizer	Aerosol
Viscosity, kinematic	Not available

Ethyl Acetate (141-78-6)

Animal studies and expert judgment for classification	False
---	-------

Acrylic Resin

Animal studies and expert judgment for classification	False
Viscosity, kinematic	1000 – 3000 mm ² /s @ 25degC.

High Mol Wt Wetting Agent

Animal studies and expert judgment for classification	False
Viscosity, kinematic	≈ 182 mm ² /s

Aerosol Ethanol 100%

Animal studies and expert judgment for classification	False
---	-------

SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

12.1. Ecotoxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

Ethyl Acetate (141-78-6)

EC50 - Other aquatic organisms [1]	717 mg/l waterflea
EC50 - Other aquatic organisms [2]	3300 mg/l

High Mol Wt Wetting Agent

LOEC (acute)	1 – 10 mg/l
BCF - Other aquatic organisms [2]	≥ 500 mg/l
Partition coefficient n-octanol/water (Log Kow)	≥ 4

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Spot Marking Paint - Black, Red, Blue, Green, Yellow, White, Orange, Grey, Purple, Lemon, Cream

Partition coefficient n-octanol/water (Log Pow)	Not available
---	---------------

Spot Marking Paint - Black, Red, Blue, Green, Yellow, White, Orange, Grey, Purple, Lemon, Cream

Safety Data Sheet

according to the WHS Regulations

High Mol Wt Wetting Agent

BCF - Other aquatic organisms [2]	≥ 500 mg/l
Partition coefficient n-octanol/water (Log Kow)	≥ 4

12.4. Mobility in soil

Spot Marking Paint - Black, Red, Blue, Green, Yellow, White, Orange, Grey, Purple, Lemon, Cream

Partition coefficient n-octanol/water (Log Pow)	Not available
---	---------------

High Mol Wt Wetting Agent

Partition coefficient n-octanol/water (Log Kow)	≥ 4
---	-----

12.5. Other adverse effects

Ozone	: Not classified
Other adverse effects	: No additional information available

Spot Marking Paint - Black, Red, Blue, Green, Yellow, White, Orange, Grey, Purple, Lemon, Cream

Fluorinated greenhouse gases	False
------------------------------	-------

Ethyl Acetate (141-78-6)

Fluorinated greenhouse gases	False
------------------------------	-------

Acrylic Resin

Fluorinated greenhouse gases	False
------------------------------	-------

High Mol Wt Wetting Agent

Fluorinated greenhouse gases	False
------------------------------	-------

Aerosol Ethanol 100%

Fluorinated greenhouse gases	False
------------------------------	-------

SECTION 13: Disposal considerations

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
-------------------------	---

SECTION 14: Transport information

ADG	IMDG	IATA
14.1. UN number		
1950	1950	1950
14.2. UN Proper Shipping Name		
AEROSOLS	AEROSOLS	Aerosols, flammable
14.3. Transport hazard class(es)		
2.1	2.1	2.1
		

Spot Marking Paint - Black, Red, Blue, Green, Yellow, White, Orange, Grey, Purple, Lemon, Cream

Safety Data Sheet

according to the WHS Regulations

ADG	IMDG	IATA
14.4. Packing group		
Not applicable	Not applicable	Not applicable
14.5. Environmental hazards		
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No

14.6. Special precautions for user

Specific storage requirement : No data available
Shock sensitivity : No data available

14.7. Additional information

Other information : No supplementary information available

Transport by road and rail

UN-No. (ADG) : 1950
Special provision (ADG) : 63, 190, 277, 327, 344, 381
Limited quantities (ADG) : See SP 277
Excepted quantities (ADG) : E0
Packing instructions (ADG) : P207, LP200
Special packing provisions (ADG) : PP87, L2

Transport by sea

UN-No. (IMDG) : 1950
Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959
Packing instructions (IMDG) : P207, LP200
Special packing provisions (IMDG) : PP87, L2
EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG) : None
Stowage and handling (IMDG) : SW1, SW22
Segregation (IMDG) : SG69

Air transport

UN-No. (IATA) : 1950
PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Y203
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 203
PCA max net quantity (IATA) : 75kg
CAO packing instructions (IATA) : 203
CAO max net quantity (IATA) : 150kg
Special provisions (IATA) : A145, A167, A802
ERG code (IATA) : 10L

14.8. Hazchem or Emergency Action Code

Hazchem Code : Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question

Australian Industrial Chemicals Introduction Scheme (AICIS)

Australian Inventory of Industrial Chemicals (AICIS) : Listed
Inventory status

Spot Marking Paint - Black, Red, Blue, Green, Yellow, White, Orange, Grey, Purple, Lemon, Cream

Safety Data Sheet

according to the WHS Regulations

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Relevant Poisons Schedule number : Unscheduled

15.2. International agreements

No additional information available

SECTION 16: Other information

Indication of changes:

Update of the SDS from former GHS version to the 7th edition of the GHS (GHS 7).

Data sources : Safe Work Australia - Code of Practice - Preparation of Safety Data Sheets for Hazardous Chemicals
Safe Work Australia - Code of Practice - Labelling of Workplace Hazardous Chemicals
Safe Work Australia - Workplace Exposure Standards for Airborne Contaminants
Safe Work Australia - Hazardous Chemical Information System (HCIS)
Australian Inventory of Industrial Chemicals (AICIS Inventory)
Environmental Protection Authority - Hazardous Substances (Hazard Classification) Notice 2020
Environmental Protection Authority - Hazardous Substances (Safety Data Sheets) Notice 2017
Environmental Protection Authority - Hazardous Substances (Labelling) Notice 2017
New Zealand - Chemical Classification and Information Database (CCID)
New Zealand - Inventory of Chemicals (NZIoC)
European Chemicals Agency (ECHA) - Annex VI (C&L Inventory)
European Chemicals Agency (ECHA) - REACH Study Results
European Chemicals Agency (ECHA) - REACH Registration Dossiers
United Nations - Globally Harmonised System of Classification and Labelling of Chemicals (GHS)
Uniform Scheduling of Medicines and Poisons (SUSMP)
United Nations Recommendations on the Transport of Dangerous Goods (UNRTDG Model Regulation)
Australian Dangerous Goods Code (ADG Code)
International Air Transport Association Dangerous Goods Regulations (IATA DGR)
International Maritime Dangerous Goods (IMDG Code).

Date of revision : 12/07/2023

Classification

Aerosol 1	H222;H229
Eye Irrit. 2A	H319
STOT SE 3	H336

Full text of H-statements

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aerosol 1	Aerosol, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Eye Irrit. 2B	Serious eye damage/eye irritation, Category 2B
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3

Spot Marking Paint - Black, Red, Blue, Green, Yellow, White, Orange, Grey, Purple, Lemon, Cream

Safety Data Sheet

according to the WHS Regulations

Full text of H-statements	
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H320	Causes eye irritation
H336	May cause drowsiness or dizziness
H373	May cause damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long lasting effects

Safety Data Sheet (SDS), Australia

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.